WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 37891
Permit No.
Basin 87-

NOTICE OF INTENT NO. 17598

1. OWNER Advanced Scientific Solutions
MAILING ADDRESS 3983 S. McCarran Blvd, Ste 201
Reno, Nevada 89502

ADDRESS AT WELL LOCATION Teet, Inc.
1750 Marietta Way
Sparks, NV

2. LOCATION NE ¼ NE ¼ Sec. 17 T 19 N N/S R 20 E Washoe County

PERMIT NO. MO#374 MW2 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Grey Brown Silty Sand (SM), with gravel loose to medium dense moist, FILL		0	11	11
Brown Sandy Gravel (GP) with abundant cobbles, medium dense, saturated scattered boulder sized clasts		11	30	19

'92 APR -6 P 1:56
STATE ENGINEER

Date started 6/3/91, 19
Date completed same, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 28 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9 5/16 Inches	0 Feet	30 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	0	28
4" End cap				
4" Lockin cap				

Perforations:
Type perforation factory sawed slot
Size perforation .020 x 1 1/2 x 6 rows
From 7 feet to 28 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal bentonite 1 foot
Placement Method: [X] Pumped [ ] Poured
6 feet
Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 7 feet to 30 feet

9. WATER LEVEL
Static water level 12½ (7/17/91) feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370, Reno NV 89510 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed Gary C. Helmer (By driller performing actual drilling on site or contractor)
Date March 30, 1992

(Rev. 3 91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 37872
Permit No.
Basin 87

NOTICE OF INTENT NO. 17598

1. OWNER Advanced Scientific Solutions
MAILING ADDRESS 3983 S. McCarran, Ste 201
Reno, NV 89502

ADDRESS AT WELL LOCATION Teet, Inc.
1750 Marietta Way
Sparks, Nevada

2. LOCATION NE ¼ NE ¼ Sec. 17 T. 19N N/S R. 20 E. Washoe County
PERMIT NO. MO#374 MW 3 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphaltic Concrete		0	2½"	2½"
Dark Brown Gravelly sand (SP) medium dense moist, FILL		2½"	12	9½
Brown Sandy Gravel (GP) with abundant cobbles, medium dense, saturated scattered boulder sized clasts		12	30	18

Date started 5.31.91, 19
Date completed Same, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 28 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5.16 Inches		0 Feet	30 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	0	28
4" End Plug				
4" Locking Cap				

Perforations:
Type perforation factory sawed slot
Size perforation .020 x 1½ x 6 rows
From 7 feet to 28 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal bentonite 2 feet
Placement Method: [X] Pumped [ ] Poured 5 foot
Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 7 feet to 30 feet

9. WATER LEVEL
Static water level 12½ (7/17/91) feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370, Reno, NV 89510 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed (By driller performing actual drilling on site or contractor)
Date March 30, 1992

'92 APR -6 P1:56
STATE ENGINEER'S OFFICE

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627