



PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 17598

1. OWNER Advanced Scientific Solutions ADDRESS AT WELL LOCATION Teet, Inc.  
 MAILING ADDRESS 3983 S. McCarran, Ste 201 1750 Marietta Way  
Reno, NV 89502 Sparks, Nevada

2. LOCATION NE 1/4 NE 1/4 Sec 17 T 19N N/S R 20 E Washoe County  
 PERMIT NO. MO#374 MW-3  
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other Tubex 190

6. LITHOLOGIC LOG

| Material  | Water Strata | From   | To     | Thick-ness |
|---|--------------|--------|--------|------------|
| Asphaltic Concrete  |              | 0      | 2 1/2" | 2 1/2"     |
| Dark Brown Gravelly sand (SP) medium dense moist, FILL  |              | 2 1/2" | 12     | 9 1/2"     |
| Brown Sandy Gravel (GP) with abundant cobbles, medium dense, saturated scattered boulder sized clasts |              | 12     | 30     | 18         |

8. WELL CONSTRUCTION  
 Depth Drilled 30 Feet Depth Cased 28 Feet

HOLE DIAMETER (BIT SIZE)  
 From To  
9 5/16 Inches 0 Feet 30 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 4" PVC             |                     | SCH 40                  | 0           | 28        |
| 4" End Plug        |                     |                         |             |           |
| 4" Locking Cap     |                     |                         |             |           |

Perforations:  
 Type perforation factory sawed slot  
 Size perforation 020 x 1 1/2 x 6 rows  
 From 7 feet to 28 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal bentonite 2 feet  Neat Cement  
 Placement Method:  Pumped 5 foot  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No  
 From 7 feet to 30 feet

1992 APR -6 P 1:56  
 RECEIVED  
 STATE ENGINEERS OF NV

Date started 5.31.91 19\_\_\_\_  
 Date completed Same 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|--------|-------------------------------|--------------|
|        |                               |              |
|        |                               |              |
|        |                               |              |
|        |                               |              |
|        |                               |              |
|        |                               |              |

9. WATER LEVEL  
 Static water level 12 1/2 (7/17/91) feet below land surface  
 Artesian flow not known G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Wayne Drilling, Inc.  
 Contractor  
 Address P.O. Box 12370, Reno, NV 89510  
 Contractor

Nevada contractor's license number issued by the State Contractor's Board 22549  
 Nevada driller's license number issued by the Division of Water Resources the on-site driller 908

Signed Wayne Drilling, Inc.  
 By driller performing actual drilling on site or contractor  
 Date March 30, 1992