c/m/93

Log# 38599
Permit#
Basin 4-48

R.D. Reynolds Drilling Company
P.O. Box 402
Wells, Nevada 89835
(702)752-3205

August 9, [illegible]

State of Nevada
Department of Conservation & Natural Resources
Office of the State Engineer
Division of Water Resources
123 W Nye Lane
Carson City, NV 89706-0940

Dear Sir:

This letter is to inform you of the abandonment of a 6" industrial well drilled for Freeman Construction permit #C-115. Location of the well: NE1-8 of Sw [illegible] Section [illegible] R56E.

First, casing was perforated from 40' to 460'. Casing below this level was screen. Next a bentonite fluid was circulated from 530', entering hole at a viscosity of [illegible] until discharged fluid from well was at 63 viscosity, mud weight was [illegible]. Hole was kept full as drill pipe was removed [illegible]. Clear water pumped to remove mud from casing. Drill pipe was removed and [illegible] hole plug was added to produce a bentonite plug from [illegible]. At this point a concrete grout was tremmied from 56' to surface. [illegible] plugging procedure. Start 7/27/93 end 8/2/93.

Thank you for your time in this matter.

Sincerely,

Anthony G. Logan

Anthony G. Logan
Nevada Drillers License #1794

[illegible]