WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 38642
Permit No.
Basin 70

NOTICE OF INTENT NO. 18728

1. OWNER David Sant
MAILING ADDRESS P.O. Box 925
Winnemucca Nevada 89446

ADDRESS AT WELL LOCATION 5115 E 2nd /Street
Winnemucca, Nevada 89446

2. LOCATION nw ¼ nw ¼ Sec. 16 T. 36 N/S R. 38 E/W Humboldt County
PERMIT NO. N/A (Issued by Water Resources) | 10-272-11 (Parcel No.) | - (Subdivision Name)

3. WORK PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[x] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [x] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Topsoil		0	2	2
Silt		2	5	3
Sandy Clay		5	25	20
Course Sand and Clay		25	30	5
Clay		30	35	5
Gravel	x	35	55	20
Clay mixed in Gravel	x	55	62	7
Gravel	x	62	68	6
Gravel w/s Clay	x	68	82	14
Course sand and Gravel	x	82	100	18

92 FEB 21 P1:22 STATE ENGINEER'S OFFICE

Date started Feb. 13, 1992, 19.92
Date completed Feb. 13, 19.92

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30/35	air on rig	

8. WELL CONSTRUCTION
Depth Drilled 100 Feet Depth Cased 95 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
10	0	100

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
65/8	6.249	.188	+2	54

Perforations:
Type perforation Mill Slot
Size perforation 1/8 x2
From 54 feet to 95 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [x] Yes [ ] No
Depth of Seal 50
Placement Method: [x] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [x] Cement Grout [ ] Concrete Grout
Gravel Packed: [x] Yes [ ] No
From 50 feet to 100 feet

9. WATER LEVEL
Static water level 20 feet below land surface
Artesian flow - G.P.M. - P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling and Pump Co. (Contractor)
Address P.O.Box 590 (Contractor)
Winnemucca, Nevada 89446-0590
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed (By driller performing actual drilling on site or contractor)
Date

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O) 627