WHITE–DIVISION OF WATER RESOURCES
CANARY–CLIENT'S COPY
PINK–WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 38647
Permit No.
Basin 83

NOTICE OF INTENT NO. 18843

1. OWNER STEVE & CINDY WALDOW
MAILING ADDRESS 3836 West 134th Street
Hawthorne CA. 90250

ADDRESS AT WELL LOCATION 230 Barrel Springs Road
Virginia City, NV

2. LOCATION NE ¼ SE ¼ Sec. 3 T. 17N N/S R. 21 E. Storey County
PERMIT NO. (Issued by Water Resources) 4-271-47 (Parcel No.) Virginia City Ranches (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Gray volcanic rock		1	138	137
Brown volcanic rock		138	191	53
Red volcanic rock		191	230	39
Brown volcanic rock		230	480	250
Gray volcanic rock		480	515	35
Small fracture(app 5GPM)	X	515	516	1
Gray volcanic rock		516	546	30
FRacture	X	546	560	14
Gray volcanic rock		560	571	11
Fracture	X	571	580	9
Gray volcanic rock		580	600	20

'92 MAR 11 A11:30
RECEIVED
STATE ENGINEER'S OFFICE

Date started 2-24-92, 19
Date completed 2-28-92, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 600 Feet Depth Cased 600 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	600 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	0	600

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 534 feet to 554 feet
From 574 feet to 594 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured

Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 600 feet

9. WATER LEVEL
Static water level 480 feet below land surface
Artesian flow 25 G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370, Reno, NV 89510 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on site driller 923
Signed (By driller performing actual drilling on site or contractor)
Date March 2, 1992

(Rev 3-90)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627