

Log# 38769
Basin# 44



MOUNTAIN CITY STAR ROUTE
ELKO, NEVADA 89801
TELEPHONE: 702-758-9234
FAX: 702-758-9204

September 23, 1992

Thomas K. Gallagher, P. E.
Hydraulic Engineer III
Department of Conservation
and Natural Resources
Division of Water Resources
123 W. Nye Lane
Carson City, Nevada 89710

Re: W-362-A

Dear Mr. Gallagher:

As requested in your Water Well Waiver W-362-A, enclosed is a copy of the plugging report for the dry well drilled in SW 1/4 SE 1/4 of Section 7, T40N, R54E, MDB&M.

We will now proceed with drilling at an alternate site.

If you have any questions, please call.

Sincerely,

Bill A. Madsen
Field Foreman

BAM/scp

Enc.

xc: Mike Jones w/enc.
Files

Hole Number: SH DWW

Coordinates: 2212 North East

Location: 1/4 Section SW 1/4 SE 1/4 Township 40N Range 54E
SEC 7

Date drilled: 7-8 - 7-12-92

Drilled by: Hackworth

Depth: 430 feet

Aquifers encountered: feet feet None
(check box)

Date plugged: 7-31-92 Plugged by: Flanders
(print)

Plugging material was introduced: From top
(check one box) Circulated
 Lifts (due to lost circulation)

Describe method of plugging (include product used, amount dry, amount wet, pounds per gallon, viscosity, etc).
330 Bags Portland well Plug 16500 LB
13 Bags Sakrete cement 10 Plug 1170 LB

Surface seal: 10 feet of neat cement (per NRS-534.150)

Discrepancies and remarks: Dry water well

Signature: Ryan J. McLeod (certifies statements to be true)

HOLE ABANDONMENT REPORT

PERMIT 57171
2212 - 19

Hole Number: SH DWW

NO TD
NO LOCATION

SEE
LOG #
38769

Coordinates: 2212 North

East

FILE IN

Location: 1/4 Section SW 4 SE 4 Q7

Township N 40

Range E 54

Date drilled: 92

TKB

Drilled by: Hackworth

Depth: feet

Aquifers encountered: feet

 feet

None
(check box)

Date plugged: 7-31-92

Plugged by: Flendri
(print)

Plugging material was introduced: From top
(check one box)

Circulated

Lifts (due to lost circulation)

Describe method of plugging (include product used, amount dry, amount wet, pounds per gallon, viscosity, etc).

330 Bags Portland Cement well Plug 16500 LB

13 Bags Sakrete cement 10 Plug 1170 LB

Surface seal: 10 feet of neat cement (per NRS-534.150)

Discrepancies and remarks:
Dry water well

Signature: Ryan J. McCarth (certifies statements to be true)