WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 38793
Permit No.
Basin 084

NOTICE OF INTENT NO. 19987

1. OWNER Groundwater Res. Cons. Inc.
MAILING ADDRESS 1735 Ft. Lowell Rd. Ste 4, Tucson, AZ 85719
ADDRESS AT WELL LOCATION Rocketdyne 2555 Whisky Springs Rd., Warm Springs (Palomino Valley) NV

2. LOCATION SW ¼ SE ¼ Sec 12 T 22N N/S R 21 E Washoe County
PERMIT NO. M/O 431-B D-27A (Issued by Water Resources) 77-110-01 (Parcel No.) Palomino Valley #12-21-5 Unit 1 (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [X] Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clayey gravelly sand Brown, well graded subangular, loose uncemented		0	23	23
Sandy Clay, Orange-brown, moderately graded, compact uncemented		23	26	3
Welded tuff, Red-grey welded rhyolite tuff		26	29.1	3.1

Date started 6/4/92, 19
Date completed 6/5/92, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			

8. WELL CONSTRUCTION
Depth Drilled 29.1 Feet Depth Cased 29.1 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches		0 Feet	29.1 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5 PVC		SCH 40	0	29.1
4.5 PVC	end cap	centralizers at 15,		29
4.5 PVC	locking	cap		

Perforations:
Type perforation factory sawed slot
Size perforation .020 x 3"
From 14.1 feet to 29.1 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal bentonite 2' 10'
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 12 feet to 29.1 #3 sand Lonestar feet

9. WATER LEVEL
Static water level not known feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature n/k °F Quality n/k

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed Gary C. Hedman (By driller performing actual drilling on site or contractor)
Date June 28, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O) 627