

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 19681

1. OWNER Groundwater Res. Consultants, Inc. ADDRESS AT WELL LOCATION Rocketdyne  
 MAILING ADDRESS 1735 E. Ft. Lowell Rd. Ste. 4 2555 Whisky Springs Rd.  
 Tucson, AZ 85719 Warm Springs (Palomino Valley) NV  
 2. LOCATION SE 1/4 SE 1/4 Sec. 12 T. 22N N/S R. 21 E. Washoe County  
 PERMIT NO. M/O 431-B D-9A 77-110-01 Palomino Valley Out 1 12-2-15  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other.....  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other. TUBEX 190

6. LITHOLOGIC LOG

| Material  | Water Strata | From | To   | Thick-ness |
|---|--------------|------|------|------------|
| Clayey gravelly silt  |              |      |      |            |
| Grey-brown, dry, well graded, angular, loose uncemented   |              | 0    | 7    | 7          |
| Gravelly clay. Tan, dry well graded, subangular loose, uncemented   |              | 7    | 9    | 2          |
| Clayey silty sand. Brown slightly moist   |              | 9    | 13   | 4          |
| Clayey gravelly sand Brown, well graded, angular, loose, uncemented, abundant silt.                                       |              | 13   | 16   | 3          |
| Clay Brown, poorly graded, dense, medium plasticity, uncemented   |              | 16   | 17   | 1          |
| Silty gravelly sand Brown, well graded, angular, loose, uncemented, abundant clay. At 23 feet cuttings become very moist. |              | 17   | 32   | 15         |
| Tuff, light yellow-brown, unwelded volcanic tuff.   |              | 32   | 38.8 | 6.8        |

8. WELL CONSTRUCTION  
 Depth Drilled 38.8 Feet Depth Cased 38.8 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 0 Feet To 38.8 Feet  
 9 5/16 Inches  
 CASING SCHEDULE  

| I. D. Size O.D. (Inches)              | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---------------------------------------|---------------------|-------------------------|-------------|-----------|
| 4" PVC                                |                     | SCH 40                  |             |           |
| 4" PVC end cap centralizers at 18, 38 |                     |                         |             |           |
| 4" PVC locking cap                    |                     |                         |             |           |

 Perforations: factory sawed slot  
 Type perforation.....  
 Size perforation .020 x 3  
 From 18.8 feet to 38.8 feet  
 Surface Seal:  Yes  No Seal Type:  Neat Cement  
 Depth of Seal bentonite pellets 2' 13'  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No #3 sand  
 From 15 feet to 38.8 7 bags 0 feet

Date started 4/3/92, 19.....  
 Date completed 4/3/92, 19.....

7. WELL TEST DATA

| TEST METHOD:  | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|--------|-------------------------------|--------------|
| <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift |        |                               |              |
| NO TEST   |        |                               |              |

9. WATER LEVEL  
 Static water level dry feet below land surface  
 Artesian flow.....G.P.M.....P.S.I.  
 Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Wayne Drilling, Inc. Contractor  
 Address P.O. Box 12370 Contractor  
 Reno, NV 89510  
 Nevada contractor's license number 22549 issued by the State Contractor's Board  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
 Signed [Signature] By driller performing actual drilling on site or contractor  
 Date May 15, 1992