WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 38803
Permit No.
Basin 084

NOTICE OF INTENT NO. 17578

1. OWNER Groundwater Resources Consult. Inc.
MAILING ADDRESS 1735 East Fort Lowell Rd. Ste 4
Tucson, Arizona 85719

ADDRESS AT WELL LOCATION Rocketdyne Ave. D
2755 Whisky Springs Rd.
Warm Springs (Palomino) Valley

2. LOCATION SW ¼ SE ¼ Sec 7 T 22N N/S R 22E E Washoe County
PERMIT NO. M-0 431 D-2A Issued by Water Resources
77-320-04 ic Parcel No.
~~Rocketdyne, NV Field Lab,~~ Palomino Valley ~~NV~~ Subdivision Name Durell 7-2-24

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☒ Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Glayey gravelly sand				
Brown, coarse sand				
with abundand gravel				
of mixed tuff fragments.				
Well graded, angular				
uncemented.		0	24	24
@ 11' Becomes more red-				
brown with increased				
clay and less gravel				
@ 21' Cuttings are wet				
Tuff. Light green,				
unwelded tuff		24	28	2

Date started 08/08/91, 19
Date completed same, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NO TEST		

8. WELL CONSTRUCTION
Depth Drilled 28 Feet Depth Cased 25.9 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches	0 Feet	28 Feet	
Inches	Feet	Feet	
Inches	Feet	Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5" PVC		SCH 40	0	28
4.5" PVC end cap/centralisers at 15', 25'				
4.5" PVC locking cap				

Perforations:
Type perforation factory sawed slot
Size perforation .020 x 1½ x 6 rows
From 15.9 feet to 25.9 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 2' bentonite 2'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 11' feet to 28' 6 bags #3 sand feet

9. WATER LEVEL
Static water level 25.37 (8/13/92) feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature n/k °F Quality not known

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. Contractor
Address P.O. Box 12370, Reno, NV 89510 Contractor

Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] By driller performing actual drilling on site or contractor
Date April 10, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627