

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT
 Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

Page 1 of 2 pages 19994
 NOTICE OF INTENT NO.

1. OWNER Groundwater Resources Consultants, Inc. ADDRESS AT WELL LOCATION Rocket-Dyne Reno
 MAILING ADDRESS 1735 E. Fort Lowell Road, Suite 4 Whiskey Springs Road 2885
Tucson, Arizona 85719 Warm Springs Valley, Reno, NV
 2. LOCATION SE 1/4 SW 1/4 Sec. 7 T. 22N N/S R. 22 E. Washoe County
 PERMIT NO. M/O #431-B D-18A 77-320-02 Palomino Valley Unit 11 7225
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other TUBEX 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sitly sand: Med. brown, dry, some clay & gravel, moderate to poor gradation, loose uncemented At. 6' clay contend increaseing		0	9	9
Gravelly clayey sand: red brn, slightly moist, contains some clay interlayers, moderate gradation, subangular, compact, slight plasticity, uncemented		9	16	7
Sandy clay: Light brn, slightly moist, some gravel, dense, low plasticity, uncemented		16	23	7
Gravelly clayey sand: Med. brn., slightly moist, moderate gradation, subang., loose slight plasticity, uncemented		23	35	12
Sandy clayey gravel: Med. brn., moist, well graded, subang. compact, slightly plasticity, uncemented.		35	47	12

8. WELL CONSTRUCTION
 Depth Drilled 58.9 Feet Depth Cased 58.9 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
9 5/16 Inches 0 Feet 58.9 Feet
InchesFeetFeet
InchesFeetFeet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5" PVC		sch 40	stick up 1.6	58.9'

PVC end cap & locking cap
 centralizers @ 29 & 58' Monument

Perforations:
 Type perforation factory sawed slot
 Size perforation .020 x 3"
 From 28.4 feet to 58.9 feet
 Fromfeet tofeet
 Fromfeet tofeet
 Fromfeet tofeet
 Fromfeet tofeet

Surface Seal: Yes No Seal Type:
 Depth of Seal 2' bentonite 21' Neat Cement
 Cement Grout
 Placement Method: Pumped Poured Concrete Grout
 Gravel Packed: Yes No #3 sand Lone Star
 From 23 feet to 58.9 feet

9. WATER LEVEL
 Static water level 46.1 (4-15-92) feet below land surface
 Artesian flow not known G.P.M. P.S.I.
 Water temperature not/k °F Quality not known

Continued page 2 of 2 pages
 Date started 4-15-92, 19.....
 Date completed 4-15-92, 19.....

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No test			

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, NV 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed Jerry D. Helman
 By Driller performing actual drilling on site or contractor
 Date June 26, 1992

