

STATE OF NEVADA
 DIVISION OF WATER RESOURCES

OFFICE USE ONLY
 Log No. 38825
 Permit No. 6-87 TRAC
 Basin Truckee Meadows
 NOTICE OF INTENT NO. 17261

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER David Keith Todd, Cons. Eng. Inc. ADDRESS AT WELL LOCATION Time Oil
 MAILING ADDRESS 2914 Domingo Ave. Sparks, Nevada

2. LOCATION NW 1/4 NW 1/4 Sec 9 T 19N N/S R 20 E Washoe County
 PERMIT NO. M/O 440 TO-7 Tank Farm, Sparks, Nevada
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Fill material, metal debris, dark stained soil, bricks		0	3	3
Cement pad, unreinforced		3	4.5	1.5
Silty sand, 80% fine-med. sand, 20% silt, 10yr brown		4.5	7	2.5
Gravel/cobbles, <10% sand and fines. Gravel 1/2-6", mafic, well rounded. Gravels clean		7	11.5	4.5
2.5y5/2 dark grayish br. Sandy gravel, 90% gravel 1/4-4", well rounded, clean. Sand is med.-coarse 5Y3/2 dk olive gray		11.5	41	27.5
Color Change (brown) at 18feet. Up to 10% silt at 19 ft. lighter colored 2.5Y5/4 light olive brown.				
Sandy gravel, 90% gravel 1/4-4" urib stained clsts 2.5y5/4 lt olive brown		30	41	11
Sand, 95% medium to coarse sand, 5% silt 2.5y5/4 lt. olive brown		41	44	3
Sand heaved to 40'				

8. WELL CONSTRUCTION
 Depth Drilled 44 Feet Depth Cased 40 Feet
 HOLE DIAMETER (BIT SIZE)
 From 9 5/16 Inches To 44 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

I.D. CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	0	44
4" PVC end cap/centralisers				
4" PVC locking cap				

Perforations:
 Type perforation factory sawed slot
 Size perforation .020 x 1 1/2 x 6 rows
 From 15 feet to 40 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 2' bentonite 11' Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No
 From 13 feet to 40 #3 sand feet

Date started 8/14/91, 19.....
 Date completed same, 19.....

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>NO TEST</u>			

9. WATER LEVEL
 Static water level 24' feet below land surface
 Artesian flow not known G.P.M. _____ P.S.I. _____
 Water temperature n/k °F Quality not known

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc.
 Address P.O. Box 12370, Reno, NV 89510
 Nevada contractor's license number 22549
 issued by the State Contractor's Board.
 Nevada driller's license number 908
 issued by the Division of Water Resources, the on-site driller.
 Signed Wayne C. Adams
 By driller performing actual drilling on site or contractor
 Date April 8, 1992