WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 38848
Permit No.
Basin 011

NOTICE OF INTENT NO. 15387

1. OWNER Hydro-Search, Inc.
MAILING ADDRESS 5259 S. Virginia St. Ste 280
Reno, Nevada 89502

ADDRESS AT WELL LOCATION Wells Manufacturing
2 Erik Circle
Verdi, Nevada

2. LOCATION SE ¼ SE ¼ Sec 8 T 19N N/S R 18 E Washoe County

PERMIT NO. M/O 363 MW-3A
Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☒ Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy, clayey gravel 20% clay, dark brown		0	3	3
Gravel, coarse, basalt clasts, 0-5% clay		3	5	2
Gravel, 10% sand, 0-5% clay, basalt clasts		5	10	5
Silty clay, medium stiff very dark grayish brown		10	16	6

Date started 3/12/91, 19
Date completed same, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 16 Feet Depth Cased 16 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches	0 Feet	16 Feet	
Inches	Feet	Feet	
Inches	Feet	Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC		SCH 40	0	16
2" PVC end cap				
2" PVC locking cap				

Perforations:
Type perforation factory sawed slot
Size perforation .020 x 1¼ x 3 rows
From 4.6 feet to 12 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 2.5-3.5 bentonite pellets
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout 0-2.5 and 12-16 ft
Gravel Packed: ☒ Yes ☐ No
From 3.5 feet to 12 (#3 sand) feet

9. WATER LEVEL
Static water level 5.06 (3/18/91) feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature 52 °F Quality not known

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Nox 12370, Reno, Nevada 89510 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date March 31, 1992

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O) 627