

STATE OF NEVADA
 DIVISION OF WATER RESOURCES

OFFICE USE ONLY
 Log No. 39086
 Permit No. _____
 Basin 603

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 19378

1. OWNER BARRICK GOLD STRIKE ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINE SITE
 MAILING ADDRESS P.O. BOX 29
ELKO, NV 89803

2. LOCATION SE 1/4 SE 1/4 Sec 5 T 36 N 49 R 49 E EUREKA County
 PERMIT NOWAIVER # M/0413A Parcel No. N/A Subdivision Name N/A
Issued by Water Resources

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|--------------------|--------------|------|------|------------|
| SAND-GRAVEL-CARLIN | 0 | 0 | 300 | 300 |
| CLAY | | 300 | 310 | 10 |
| SAND-GRAVEL-CARLIN | | 310 | 400 | 90 |
| CLAY | | 400 | 500 | 100 |
| CHERT | | 500 | 505 | 5 |
| CLAY | | 505 | 640 | 135 |
| LIMESTONES | | 640 | 1140 | 500 |

8. WELL CONSTRUCTION
 Depth Drilled 1140 Feet Depth Cased 1140 Feet

HOLE DIAMETER (BIT SIZE)

| Inches | From | To |
|---------------|-----------|-------------|
| <u>12 1/4</u> | <u>0</u> | <u>65</u> |
| <u>6 1/2</u> | <u>65</u> | <u>1140</u> |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-------------|
| <u>7</u> | <u>38</u> | <u>.375</u> | <u>0</u> | <u>65</u> |
| <u>1 1/4</u> | <u>2.25</u> | <u>.140</u> | <u>0</u> | <u>1140</u> |
| <u>1 1/4</u> | <u>2.25</u> | <u>.140</u> | <u>0</u> | <u>400</u> |

Perforations:
 Type perforation DRILLED HOLES
 Size perforation 1/8"
 From 300 feet to 400 feet
 From 840 feet to 1140 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 65 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No
 From 1 1140-820 feet to 2 400-280 feet

9. WATER LEVEL
 Static water level 972 feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature _____ °F Quality _____

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING Contractor
 Address 2286 WEST 1500 SOUTH Contractor
SALT LAKE CITY, UTAH 84104
 Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1410
 Signed John V. Morgan
 By driller performing actual drilling on site or contractor
 Date APRIL 22, 1992

Date started APRIL 16 1992
 Date completed APRIL 22 1992

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|-----------|-------------------------------|--------------|
| <u>25</u> | | |

92 MAY -8 P12 32
 RECEIVED
 STATE ENGINEERS OFFICE