WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

DUAL COMPLETION
PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

PZ-92-5

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39098
Permit No.
Basin 61

NOTICE OF INTENT NO. 19373

1. OWNER BARRICK GOLD STRIKE
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION SW ¼ NW ¼ Sec. 30 T. 36 N/S R. 50 E. EUREKA County
PERMIT NO. M/0441 (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
CLAY SEAMS, WEATHERED		0	140	
DIONITE				140
WEATHERED DIONITE		140	450	310
DIONITE-GRAY	12	450	600	150

92 APR 14 A9:51
STATE ENGINEER'S OFFICE

Date started MARCH 28, 19 92
Date completed APRIL 1, 19 92

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
12		

8. WELL CONSTRUCTION
Depth Drilled 600 Feet Depth Cased 600 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12.25 Inches		0 Feet	57 Feet
6.50 Inches		57 Feet	600 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7.00	38	.500	0	57
1.25	.225	.140	0	600
1.25	.225	.140	0	435

Perforations:
Type perforation DRILLED
Size perforation 1/8"
From 1. 600 feet to 560 feet
From 2. 435 feet to 330 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 57'
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 1. 600-536 feet to 2. 436-302 feet

9. WATER LEVEL
Static water level 403 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature 62 °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 W 1500 S SLC, UT 84104 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1794
Signed Tony Logan (By driller performing actual drilling on site or contractor)
Date APRIL 1, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627