WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PZ92-92

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39102
Permit No.
Basin 61

NOTICE OF INTENT No. 19380

1. OWNER BARRICK GOLD STRIKE
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89801

ADDRESS AT WELL LOCATION
BARRICK GOLD STRIKE MINE

2. LOCATION SW ¼ SW ¼ Sec. 30 T. 36 N/X R. 50 E EUREKA County
PERMIT NO. M/0441 (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BROKEN DIONITE		0	40	40
DIONITE	10	40	380	340
CLAY		380	390	10
DIONITE		390	625	235

'92 MAY 15 A0:45
STATE ENGINEER

Date started APRIL 26, 19 92
Date completed APRIL 29, 19 92

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25		

8. WELL CONSTRUCTION
Depth Drilled 625 Feet Depth Cased 620 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12½	Inches	0	Feet	20	Feet
6.200	Inches	20	Feet	625	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7	26	.375	0	20
1.25	2.25	.140	0	620

Perforations:
Type perforation DRILLED
Size perforation 1/8"
From 1. 580 feet to 620 feet
From 2. 235 feet to 275 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 60
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 1. 560 TO 625 feet to 2. 220 TO 280 feet

9. WATER LEVEL
Static water level 184 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature 60 °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1410
Signed (By driller performing actual drilling on site or contractor)
Date APRIL 30, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627