WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39217
Permit No.
Basin 090

NOTICE OF INTENT NO. 19941

1. OWNER George Gillemot
MAILING ADDRESS P.O.Box 370
Glennbrook, Nevada 89413

ADDRESS AT WELL LOCATION at a point of which SW corner of said Sec. 2 bears 50 69 30 min. 51 sec. W at a distance of 687.75'

2. LOCATION SW ¼ SW ¼ Sec. 2 T 14 N/S R 18 E Douglas County
PERMIT NO. 55683 & 55837 Issued by Water Resources
S.No. 55837 Parcel No.
– Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE fire
☒ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay / Cobbles		0	10	10
Red Clay		10	41	31
Red Rock		41	95	54
Red Shale/ Sandstone		95	175	80
Gray Sandstone		175	212	37
Fractured Granite/clay	X	212	250	38
Decomposed Granite		250	270	20
Fractured Granite	X	270	290	20
Blue Clay		290	292	2
Gray Sandstone	X	292	312	20
Brown Clay		312	318	6
Gray Sandstone		318	345	27
Hard - Dark Grey Clay		345	440	95
Hard - Blue Granite		440	450	10
Fractured Granite	X	450	480	30

Date started 5/11, 1992
Date completed 5/24, 1992

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☒ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
100	288'	6 hrs.

8. WELL CONSTRUCTION
Depth Drilled 480 Feet Depth Cased 480 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
18 3/4 Inches		0 Feet	40 Feet
12 3/4 Inches		0 Feet	225 Feet
7 7/8 Inches		225 Feet	480 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
14 3/4	27.73	.188	0	40
8 5/8	16.94	.188	0	205
6 3/4	5.25	.188	+3	140

Perforations:
Type perforation Mill Slot
Size perforation 1/8 X 2
From 205 feet to 225 8 3/4" feet
From 140 feet to 480 6 3/4" feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 480 feet

9. WATER LEVEL
Static water level 125 feet below land surface
Artesian flow – G.P.M. – P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling and Pump Co. Contractor
Address P.O.Box 590 Contractor
Winnemucca, Nevada 89446-0590

Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed [signature] By driller performing actual drilling on site or contractor
Date June - 18 - 92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627