WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39235
Permit No.
Basin 102

NOTICE OF INTENT NO.

1. OWNER Tony Laca
MAILING ADDRESS 13540 Mohhogony Dr
3120 Second St. Reno. NV 89511

ADDRESS AT WELL LOCATION
2 Nd. Street.
Silver Springs NV. 89429

2. LOCATION NE ¼ SE ¼ Sec. 9 T. 17 N/S R. 25 E. Lyon County
PERMIT NO. NA (Issued by Water Resources) 17-171-15 (Parcel No.) Lakeside #2 (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☒ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand & Gravel		0	39	39
Tan Clay Very Stickey		39	63	24
Layers, Sandstone & Clay		63	70	7
Stickey Green Clay		70	98	28
		98	103	5
Blue Clay & Sand		103	120	17
Fine Black Sand	✓	120	132	12
Blue Clay		132	155	23
Course Sand		155	158	3
Fine Black Sand & Silt.	✓	158	170	12

'92 JUN 22 P2:06
STATE ENGINEERS OFF

Date started 5/23, 1992
Date completed 5/29, 1992

7. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
300	170	12 Hrs

Had trouble with Fine Black Sand Coming Into Well,

8. WELL CONSTRUCTION
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

	From	To
11" Inches	0 Feet	68 Feet
8¾ Inches	68 Feet	170 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.00	188	+1	170

Perforations:
Type perforation Air Star Wheel Prep.
Size perforation ⅛ X 1 6# Rows
From 130 feet to 170 feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 68
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 68' feet to 170' feet

9. WATER LEVEL
Static water level 46' feet below land surface
Artesian flow NA G.P.M. NA P.S.I.
Water temperature Cold °F Quality Cloudy

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Leach Drilling Inc. (Contractor)
Address Po. Box 599 (Contractor)
Silver Springs NV. 89429
Nevada contractor's license number issued by the State Contractor's Board 031841
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1740
Signed Nathinal L. Leach (By driller performing actual drilling on site or contractor)
Date 6/17/91

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627