

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY  
 Log No. 39583  
 Permit No. 87  
 Basin.....  
 NOTICE OF INTENT NO. 18839  
 Downtown Reno

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

1. OWNER SEA Consulting Eng. Inc. ADDRESS AT WELL LOCATION Downtown Reno  
 MAILING ADDRESS 950 Industrial Way Plaza & Center, Commercial/Lake  
Sparks, NV 89431-6092 Reno, NV  
 2. LOCATION SE 1/4 NE 1/4 Sec. 11 T. 19 N/S R. 19 E. Washoe County  
 PERMIT NO. M/O 483 SE well Downtown Reno  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other.....  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other Tubex 190

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt Concrete		0	5"	5"
Base		5"	12"	7"
Moist, compact, gray and brown Cobbly Gravelly Clayey Sand with estimated 15% plastic fines, 60% fine to coarse sand 25% gravel to 3" with est. 20% by volume cobbles to 6" diam.		1	3.5	3.5
Moist dense, brown cobbly gravelly sand with est. 5-10% low plastic fines, 80% fine to coarse sand 10-50% gravel to 3" with est. 50% cobbles to 12" (by volume)		3.5	20	16.5
Brown cobbly gravelly slightly clayey sand with est. 10-15% low plastic fines, 60% sand, 25-30% gravel		20	33.8	13.8

8. WELL CONSTRUCTION  
 Depth Drilled 33.8 Feet Depth Cased 33.8 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 0 To 33.8  
9 5/16 Inches.....Feet.....Feet  
 .....Inches.....Feet.....Feet  
 .....Inches.....Feet.....Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	0	33.8
4" PVC end cap				
4" PVC locking cap				

Perforations: factory sawed slot  
 Type perforation.....  
 Size perforation .020 x 1 1/2 x 6 rows  
 From 22 feet to 32 feet  
 From.....feet to.....feet  
 From.....feet to.....feet  
 From.....feet to.....feet  
 From.....feet to.....feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 2' bentonite 14 1/2'  Neat Cement  
 Cement Grout  
 Placement Method:  Pumped  Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From.....feet to.....feet

9. WATER LEVEL  
 Static water level 25.87 feet below land surface  
 Artesian flow not known G.P.M. .... P.S.I.  
 Water temperature n/k °F Quality n/k

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. Contractor  
 Address P.O. Box 12370 Contractor  
Reno, NV 89510

Nevada contractor's license number 922549  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
 Signed [Signature]  
 by driller performing actual drilling on site or contractor  
 Date September 15, 1992

Date started 12/4/91, 19.....  
 Date completed 12/4/91, 19.....

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
<u>WC 7257</u>			