ORIGINAL

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 39849
Permit No.
Basin 92A

NOTICE OF INTENT NO. 20114

1. OWNER: BARON DICKEY
MAILING ADDRESS: 996 Hanson Crt. Milpitas, CA 95035
ADDRESS AT WELL LOCATION: 1225 Columbia Hill Road Reno, NV 89510

2. LOCATION: NE ¼ NW ¼ Sec. 6 T 21N N/S R 19 E Washoe County
PERMIT NO. (Issued by Water Resources) 079-342-22 (Parcel No.) Palomino Valley (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	2	2
Brown sandy clay		2	12	10
Green sandy clay		12	22	10
Gray sandy clay		22	90	68
Soft zone	X	90	98	8
Gray sandy clay		98	123	24
Soft zone	X	123	127	4
Gray sandy clay		127	136	9
Gray sand stone		136	155	19
Soft zone	X	155	162	7
Gray sand stone		162	175	13

Date started 11-18-92, 19
Date completed 11-19-92, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 175 Feet Depth Cased 175 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	175 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	175

Perforations:
Type perforation: factory sawed slot
Size perforation: 3/32 x 3 x 5 around
From 90 feet to 100 feet
From 120 feet to 130 feet
From 150 feet to 170 feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 175 feet

9. WATER LEVEL
Static water level 47 feet below land surface
Artesian flow 50 G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) Wayne Drilling, Inc.
Address (Contractor) P.O. Box 12370 Reno, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed (By driller performing actual drilling on site or contractor)
Date November 19, 1992

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627