

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 17966

1. OWNER BARRICK GOLDSTRIKE ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINE  
 MAILING ADDRESS PO BOX 29  
ELKO, NV 89803

2. LOCATION NE 1/4 NW 1/4 Sec. 24 T. 36 N. 49 E. EUREKA County  
 PERMIT NO. 55142 Issued by Water Resources Parcel No. N/A Subdivision Name N/A

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
BROWN ALTERED ROCK/CLAY		0	105	105
BLACK ROCK/CLAY		105	265	160
BLACK ROCK		265	660	395
BLACK ROCK/CALCITE		660	755	95
BLACK ROCK		755	780	25
ROCK/CLAY		780	840	60
BLACK ROCK		840	1015	175
BLACK ROCK/CALCITE		1015	1355	340
BLACK ROCK		1355	1765	410
BLACK ROCK/CALCITE		1765	2030	265

N 40.967533  
W 116.389533 NAD27

'92 NOV -9 P1:19  
 STATE ENGINEERS UNIT

Plugged under NDI 61694

8. WELL CONSTRUCTION  
 Depth Drilled 2030 Feet Depth Cased 2020 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
<u>48</u>	<u>0</u>	<u>68</u>
<u>31</u>	<u>68</u>	<u>2030</u>

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>40</u>	<u>159</u>	<u>.375</u>	<u>0</u>	<u>68</u>
<u>24</u>	<u>95</u>	<u>.375</u>	<u>0</u>	<u>260</u>
<u>24</u>	<u>95</u>	<u>.375</u>	<u>300</u>	<u>580</u>
<u>24</u>	<u>95</u>	<u>.375</u>	<u>620</u>	<u>940</u>
<u>24</u>	<u>95</u>	<u>.375</u>	<u>1020</u>	<u>1220</u>
<u>24</u>	<u>95</u>	<u>.375</u>	<u>1260</u>	<u>1580</u>
<u>24</u>	<u>95</u>	<u>.375</u>	<u>1980</u>	<u>2020</u>

Perforations: \_\_\_\_\_  
 Type perforation LOUVERED  
 Size perforation .125 X 2

From (feet)	To (feet)
<u>260</u>	<u>300</u>
<u>580</u>	<u>620</u>
<u>940</u>	<u>1020</u>
<u>1220</u>	<u>1260</u>
<u>1580</u>	<u>1980</u>

Surface Seal:  Yes  No Seal Type:  
 Neat Cement  
 Cement Grout  
 Concrete Grout

Depth of Seal 68

Placement Method:  Pumped  Poured

Gravel Packed:  Yes  No  
 From 100 feet to 2030 feet

9. WATER LEVEL  
 Static water level 600 feet below land surface  
 Artesian flow N/A G.P.M. N/A P.S.I.  
 Water temperature 125 °F Quality CLEAR

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name LANG EXPLORATORY DRILLING  
 Contractor  
 Address 2286 WEST 1500 SOUTH  
 Contractor  
SALT LAKE CITY, UT 84104  
 Nevada contractor's license number issued by the State Contractor's Board 0021976  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1546  
 Signed Patricia Ball  
 By driller performing actual drilling on site or contractor  
 Date OCTOBER 29, 1992

Date started SEPTEMBER 19, 19 92  
 Date completed OCTOBER 29, 19 92

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			