WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40033
Permit No.
Basin 64

NOTICE OF INTENT NO. 20431

1. OWNER Hole #TDOH-6 Marigold Mining Company
MAILING ADDRESS P. O. Box 9
Valmy, NV 89438

ADDRESS AT WELL LOCATION 14 miles west of Battle Mtn. on Interstate 80, south off Interstate, 4 miles to mine site (tailings dam

2. LOCATION NE ¼ NW ¼ Sec 9 T 33 N/S R 43 E Humboldt County

PERMIT NO. M/O 562A (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
0' to 325' TD.		0	325'	
Gravel clay				
Matrix				

'93 JAN 19 P2:29
RECEIVED
STATE ENGINEER'S OFFICE

Date started 12/3, 19 92
Date completed 12/6, 19 92

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
At 315'	1	---	1 hour

8. WELL CONSTRUCTION
Depth Drilled 325 Feet Depth Cased 315 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	20 Feet
6 Inches		20 Feet	325 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	SCH 80	SCH 80	0	315
6 5/8		5/16	0	20

Perforations:
Type perforation Horizontal slot
Size perforation .101 Perf.
From Blank 0 feet to 275 feet
From Slot 275 feet to 315 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 25'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 270 feet to 315 feet

9. WATER LEVEL
Static water level 283 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature -- °F Quality --

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name EKLUND DRILLING COMPANY, INC. (Contractor)
Address P. O. Box 2786 (Contractor)
Elko, NV 89803

Nevada contractor's license number issued by the State Contractor's Board 0030823

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1698

Signed Gary Layne Harris (By driller performing actual drilling on site or contractor)

Date 1/6/93

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40033
Permit No.
Basin 64

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Hole #TDOH-6

NOTICE OF INTENT NO. 20431

1. OWNER Marigold Mining Company
MAILING ADDRESS P. O. Box 9
Valmy, NV 89438

ADDRESS AT WELL LOCATION 14 miles west of Battle Mtn. on Interstate 80, south off Interstate, 4 miles to mine site (tailings dam area)

2. LOCATION NE ¼ NW ¼ Sec. 9 T. 33 N S R. 43 E. Humboldt County
PERMIT NO. M/O 562A (Issued by Water Resources) | Parcel No. N/A | Subdivision Name N/A

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
o' to 325' TD.		0	325	'
Gravel clay				
Matrix				

Date started 12/3, 19 92
Date completed 12/6, 19 92

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
AT 315'	1	---	1 hour

8. WELL CONSTRUCTION
Depth Drilled 325 Feet Depth Cased 315 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	20 Feet
6 Inches		20 Feet	325 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	SCH 80	SCH 80	0	315

Perforations:
Type perforation Horizontal slot
Size perforation .010 Perf.
From Blank 0 feet to 275 feet
From Slot 275 feet to 315 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 25'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 270 feet to 315 feet

9. WATER LEVEL
Static water level 283 feet below land surface
Artesian flow NO G.P.M. N/A P.S.I.
Water temperature -- °F Quality --

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name EKLUND DRILLING COMPANY, INC. (Contractor)
Address P. O. Box 2786 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1698
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 12/17/92

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627