WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40037
Permit No.
Basin 71

NOTICE OF INTENT NO. 19110

1. OWNER Ken Pavlich
MAILING ADDRESS 6380 Solar Drive
Winnemucca Nevada 89446

ADDRESS AT WELL LOCATION 6380 Solar Drive
Winnemucca Nevada

2. LOCATION NW/SE ¼ SE/SE ¼ Sec. 12 T. 35 X N/S R. 37 E. Humboldt County
PERMIT NO. N/A (Issued by Water Resources) 013513-04 (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Topsoil / Sand		0	4	4
Hard Cemented Gravel		4	120	116
Sand / Gravel	X	120	160	40
Basalt	X	160	215	55

'92 DEC 24 A10:56
STATE ENGINEER'S OFFICE

Date started Dec.10, 19 92
Date completed Dec. 12, 19 92

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50	air on rig	

8. WELL CONSTRUCTION
Depth Drilled 215 Feet Depth Cased 215 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9 7/8 Inches	0 Feet	215 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	12.92	.188	+2	120 B

Perforations:
Type perforation Mill Slot / Rotary perf mills
Size perforation 1/8 X 3 knife
From 120 feet to 215 feet
From feet to feet
From 8" - 195/215 feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 215 feet

9. WATER LEVEL
Static water level 80 feet below land surface
Artesian flow - G.P.M. - P.S.I.
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling adn Pump Co. (Contractor)
Address P.O.Box 590 (Contractor)
Winnemucca Nevada 89446-0590

Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources the on-site driller 1195
Signed (By driller performing actual drilling on site or contractor)
Date 12-21-92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627