WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 40828
Permit No.
Basin 87

NOTICE OF INTENT NO. 14419

1. ~~OWNER~~ Consultant: Enviromental Materials Inc.
MAILING ADDRESS 5930 LBJ Frwy Ste 300
Dallas, Texas 75240

Client:
ADDRESS AT WELL LOCATION Greyhound Lines Inc.
460 W. 2nd Street
Reno, NV

2. LOCATION NE ¼ SE ¼ Sec. 11 T. 19N N/S R. 19 E. Washoe County
PERMIT NO. M/O 237 MW# 5 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [X] Other ODEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Concrete		0	8"	8"
Brown, well sorted med		8"	9'	8.4
to coarse sand				
Gravel& cobbles w/fines		9	25	16

Date started April 17, 1990, 19
Date completed April 17, 1990, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NO TEST			

8. WELL CONSTRUCTION
Depth Drilled 25 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 5/8 Inches		0 Feet	25 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4		sch 40	0	10
End Cap				
Locking	Cap			

Perforations:
Type perforation Factory Slotted
Size perforation .020
From 10 feet to 25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout
Bentonite Seal @ 6-8'
Gravel Packed: [X] Yes [ ] No
From 8 feet to 25 feet

9. WATER LEVEL
Static water level 16 feet below land surface
Artesian flow not known G.P.M. P.S.I.
Water temperature n/k °F Quality n/k

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date April 12, 1993

'93 APR 19 P1:17 RECEIVED STATE ENGINEERS OFFICE

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627