WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 41604
Permit No.
Basin 087

NOTICE OF INTENT NO. 14905

1. ~~OWNER~~ Consultant: JBR Consultants Group
MAILING ADDRESS 8160 S. Highlands Dr., Suite A-4
Sandy, Utah 84093

Client:
ADDRESS AT WELL LOCATION Reno Chrysler Plymouth
2675 S. Virginia
Reno, NV.

2. LOCATION SE ¼ NW ¼ Sec. 24 T. 19N N/S R. 19 E. Washoe County

PERMIT NO. M/O-261 MW# F (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[X] Air [X] Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	2"	2"
Gravel Fill		2"	6"	4"
Dk brown clayey, silty soil		6"	2'	1'6"
Orange brown to gray, loose, very coarse clayey sand		2	7	5
Gravel, variably clayey coarse sand, gray, loose		7	22	15
Gravelly coarse sand locally clayey		22	30	8

'93 APR 29 A10:46
STATE ENGINEER'S OFFICE

Date started July 10, 1990, 19
Date completed July 10, 1990, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NO TEST			

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches		0 Feet	30 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		SCH 40	0	15
End Cap				
Locking Cap				

Perforations:
Type perforation Machine slot
Size perforation 0.020
From 15 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0-11'
Placement Method: [ ] Pumped [X] Poured
Bentonite Seal @ 11-13'
Gravel Packed: [X] Yes [ ] No
From 13 feet to 30 feet

Seal Type: 11' [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

9. WATER LEVEL
Static water level 21' feet below land surface
Artesian flow Not Known G.P.M. P.S.I.
Water temperature N/K °F Quality N/k

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NV. 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date April 27, 1993

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 3-91) (O)-627