

Abandoned

OFFICE USE ONLY

Log No. 41741 & 41742  
Permit No. 1084  
Basin. 1084

ABANDONMENT INTENT 21836  
NOTICE OF INTENT NO. 21410

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

**WELL DRILLER'S REPORT**

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER ANTHONY SHAFTON / 12-13-92 ADDRESS AT WELL LOCATION Yellow Tail  
MAILING ADDRESS 1120 Gordon / P.O. Box 14606 Reno, NV 89509/Chicago, IL 60614 Reno, NV 89510  
2. LOCATION SE 1/4 SE 1/4 Sec. 2 T. 21N N/S R. 21 E Washoe County  
PERMIT NO. 77-230-06 Parcel No. Palomino Valley Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Top soil		0	1	1
Volcanic clays with some boulders		1	21	20
Brown clay		21	60	39
Soft zone (NO WATER)		60	71	11
Brown clay		71	105	34
Soft zone (NO WATER)		105	116	11
Brown clays		116	216	100
Brown volcanic rock		216	280	64
Soft zone fracture (app 1.5 to 2 GPM)	X	280	292	12
Volcanic rock, brown		292	306	14
Soft zone (NO WATER)		306	311	5
Volcanic rock brown		311	361	50
Brown clay		361	390	29
Brown volcanic rock		390	436	46
Soft brown sandy clay		436	467	31
Brown volcanic rock (NO WATER)		467	500	33

ABANDONMENT: May 25, 1993

Trip hole. Static 225-250 ft. Bottom at 475 ft.  
Clean hole. Blow well. Est. .5 to 1 GPM w/air.  
Trip out. Pull starter pipe. Pour to top with "7 sack" cement as per Tom Gallagher's OK.  
Finish at grade.  
Location: 200 ft W of Yellow Tail  
10 ft E of driveway

8. WELL CONSTRUCTION  
Depth Drilled 500 Feet Depth Cased none Feet

HOLE DIAMETER (BIT SIZE)  
From 10 Inches 50 Feet  
From 8 5/8 Inches 500 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:  
Type perforation none installed  
Size perforation \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  
Depth of Seal Abandoned  Cement Grout  
Placement Method:  Pumped  Poured  Concrete Grout

Gravel Packed:  Yes  No  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Date started 11-9-92, 19\_\_\_\_  
Date completed 11-11-92, 19\_\_\_\_

7. WELL TEST DATA

TEST METHOD:  Bailor  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>03</u>	<u>9:56</u>	<u>03 SEP 30 AM 9:56</u>
<u>03</u>	<u>9:56</u>	<u>03 SEP 30 AM 9:56</u>

RECEIVED STATE ENGINEERS OFFICE JUN 7 1993

9. WATER LEVEL  
Static water level 225 to 250 feet below land surface  
Artesian flow 1/2 to 1 G.P.M. P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. Contractor  
Address P.O. Box 12370 Contractor  
Reno, NV 89510

Nevada contractor's license number 22549  
issued by the State Contractor's Board.

Nevada driller's license number 923  
issued by the Division of Water Resources, the on-site driller.

Signed [Signature]  
By driller performing actual drilling on site or contractor  
Date November 14, 1992