WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 42037
Permit No.
Basin 6-90
NOTICE OF INTENT NO.

1. OWNER Barta Family Estate
MAILING ADDRESS 755 Burgundy Road
Incline Village, Nevada

ADDRESS AT WELL LOCATION Les Barta
755 Burgundy Road
Incline Village, Nevada

2. LOCATION NE ¼ NE ¼ Sec. 10 T. 16 N/S R. 18 E. Washoe County
PERMIT NO. M/0-609 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ ~~Rotary~~ PVC ☐ RVC
☐ Air ☐ Other Test Pit

6. MW/TP-2 LITHOLOGIC LOG PLUGGING

Material	Water Strata	From	To	Thickness
Brown, gravelly Sand w/ cobbles and boulders	X	7.3'	10.5'	3.2'

* Note: Displaced 1.5 cubic feet of Basalite Concrete Redi-Mix from ~1' below top of casing to 10.5' depth from ground surface. Contractor will sawcut casing and seal to 1' below ground surface in 2-3 days for subgrade landscaping purposes.

Date started (Plugging) 6-29, 1993
Date completed (Plugging) 6-29, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 10.5 Feet Depth Cased 10.5 Feet

HOLE DIAMETER ~~(BIT SIZE)~~ Annular Space

Inches	From (Feet)	To (Feet)
6 3/4	0	10.5

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4	½#/ft	1/8"	0	10.5

Perforations:
Type perforation slotted
Size perforation .020 slotted PVC
From 5.0 feet to 10.0 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal ~5.0 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout
Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 7.3 feet below land surface
Artesian flow — G.P.M. P.S.I.
Water temperature 55 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name James Costalupes
Address P. O. Box 273 (Contractor)
Crystal Bay, Nv. 89402 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board NV. 21839
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M 1655
Signed Scott B. McDaniel (By driller performing actual drilling on site or contractor)
Date June 29, 1993

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627