WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 42072
Permit No.
Basin 9-106

NOTICE OF INTENT NO. 22380

1. OWNER Don E. Payne
MAILING ADDRESS
ADDRESS AT WELL LOCATION

2. LOCATION SE ¼ NW ¼ Sec. 29 T 10 (N)S R 22 (E) DOUGLAS County
PERMIT NO. (Issued by Water Resources) APN 39-132-03 (Parcel No.) TOPAZ LAKE (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOPSOIL & BOULDERS		0	1	
BOULD. & BRN CLAY		1	43	
BRN SANDY CLAY		43	47	
BOULD & BRN CLAY		47	96	
BRN CLAY		96	102	
BOULD. & BRN CLAY		102	118	
COURSE SAND & CLAY		118	123	
COBBLES W BRN CLAY		123	155	
CLAY W COBBLES EMBED.		155	178	
COURSE SAND SOME CLAY	WB	178	182	
CLAY W COB & SHP. GRAV. EMB.		182	195	
COBBLES & SHP. GRAV. S/CLAY	WB	195	245	
BRN SANDY CLAY		245	250	

JUL 19 P 2:03
STATE ENGINEER

Date started 5-26, 1993
Date completed 6-4, 1993

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
35+	90'	6 HR.

8. WELL CONSTRUCTION
Depth Drilled 250' Feet Depth Cased 250' Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
12 1/4	0	250

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8"		188	0	250

Perforations:
Type perforation FACTORY
Size perforation 3/32" x 3"
From 250 feet to 210 feet
From 210 feet to 180 feet T.C.
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 160
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 100 feet to 0 feet

9. WATER LEVEL
Static water level 90' feet below land surface
Artesian flow G.P.M. 35+ P.S.I.
Water temperature COLD °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name ED MILLER (Contractor)
Address Box 92 (Contractor)
SMITH NV 89444
Nevada contractor's license number issued by the State Contractor's Board 32166
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1535
Signed [signature] (By driller performing actual drilling on site or contractor)
Date

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627