WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 42393
Permit No.
Basin 212

NOTICE OF INTENT NO. 12110

1. OWNER LV CONVENTION & VISITORS AUTHORITY
MAILING ADDRESS C/O G.C. WALLACE, INC. 1555 SO. RAINBOW BLVD, LAS VEGAS, NV 89102
ADDRESS AT WELL LOCATION PARKING LOT OF CONVENTION CENTER SOUTH HALL ~2000' EAST OF PARADISE ROAD, 20' SOUTH OF DESERT INN ROAD

2. LOCATION NE ¼ NW ¼ Sec. 15 T. 21 N/S R. 61 E. CLARK County
PERMIT NO. MO-2332 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other AUGER

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
ASPHALT/FILL		0	1.5	1.5
SILTY SAND W/ GYPSUM		1.5	6	4.5
CALICHE		6	7	1
SANDY CLAY W/ GRAVEL		7	9	2
CEMENTED SAND & GRAV.		9	9.5	0.5
GYPSIFEROUS CLAY		9.5	12	2.5
SILTY SAND		12	17	5
CLAYEY GRAVEL W/ SAND		17	18	1
SANDY CLAY		18	20.5	2.5
CLAYEY GRAVEL		20.5	25	4.5
SILTY SAND		25	28	3
SANDY CLAY, TAN		28	35	7
CLAY, LT BRN		35	44.5	9.5
SANDY CLAY W/ GRAVEL		44.5	50	5.5

Date started SEPTEMBER 22, 19 93
Date completed SEPTEMBER 22, 19 93

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

RECEIVED
OCT 7 1993
Div. of Water Resources
Branch Office - Las Vegas, NV

8. WELL CONSTRUCTION
Depth Drilled 50 Feet Depth Cased 50 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	50 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"	0.64	0.154	0	50

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020" IN
From 5 feet to 50 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-2' 2-4' BENTONITE
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 4 feet to 50 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name RICHARD LEBLANC (Contractor)
Address 4670 SO. POLARIS AVE (Contractor)
LAS VEGAS NV 89103
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1817
Signed (By driller performing actual drilling on site or contractor)
Date 10-4-93

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627