WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 42443
Permit No.
Basin 4-53

NOTICE OF INTENT NO. 24081

1. OWNER Cominco American Resource
MAILING ADDRESS P.O. Box 847
Carlin, NV 89822

ADDRESS AT WELL LOCATION Buckhorn Mine
35 miles SW of Carlin, NV

2. LOCATION SE ¼ NW ¼ Sec. 31 T. 27 N/S R. 49 E. Eureka County

PERMIT NO. MO-587-B (Issued by Water Resources) | #BMW-40 (Parcel No.) | NA (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Clay/basalt/boulders | | 0 | 30 | 30 |
| Shale/clay | | 30 | 37 | 7 |
| Clay | | 37 | 47 | 10 |
| Shale | | 47 | 50 | 3 |
| Shale/clay | | 50 | 54 | 4 |
| Basalt | | 54 | 68 | 14 |
| Basalt/clay | | 68 | 73 | 5 |
| Basalt | | 73 | 98 | 25 |

'93 JUN 17 P2:01
STATE ENGINEER

Date started May 19, 19 93
Date completed May 19, 19 93

7. WELL TEST DATA
TEST METHOD: ☒ Bailer ☐ Pump ☐ Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|---|
| Less than | 1 | | 1 |

8. WELL CONSTRUCTION
Depth Drilled 98 Feet Depth Cased 98 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 6 Inches | | 0 Feet | 98 Feet |
| Inches | | Feet | Feet |
| Inches | | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 4 | SCH 40 | PVC | +2 | 98 |

Perforations:
Type perforation Screen
Size perforation .020
From 88 feet to 98 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 85
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 85 feet to 98 feet

9. WATER LEVEL
Static water level 79 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality did not test

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 590 (Contractor)
Winnemucca, NV 89446

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713

Signed C. E. Eppler
(By driller performing actual drilling on site or contractor)

Date 6-14-93

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627