WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 42470
Permit No.
Basin 6-85

NOTICE OF INTENT NO. 20415

1. OWNER Eugene Dembenski
MAILING ADDRESS 11375 Campo Rico Lane
Reno, nevada 89511

ADDRESS AT WELL LOCATION 11375 Campo Rico Lane
Reno nevada 89511 (Spanish Springs Valley)
(Ranches Unit #2)

2. LOCATION SW ¼ NE ¼ Sec. 23 T. 21 N/S R. 20 E. Washoe County
PERMIT NO. N/A (Issued by Water Resources) 076-400-79 (Parcel No.) Campo Rico Lane Spanish Springs Valley (Subdivision Name) Ranches Unit #2

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☑ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Course Sand		0	10	10
Brown Clay		10	30	20
Boulders and Gravels		30	38	8
Brown Clay		38	60	22
Course Sand		60	100	40
Brown Clay		100	110	10
Course Sand And Gravels		110	140	30
Course Sand And Clay		140	183	43
Tan Clay		183	210	
Course Sand	✓	210	220	10

Date started 7-19, 1993
Date completed 7-24, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Developed For 8 hours and produced about 30 Gallons a min.		

8. WELL CONSTRUCTION
Depth Drilled 220 Feet Depth Cased 220 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
11"	Inches	0	Feet	50	Feet
8 3/4	Inches	50	Feet	220	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.00	3/16	+1	220

Perforations:
Type perforation Air Perf
Size perforation
From 60 feet to 220 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-50
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 50 feet to 220 feet

9. WATER LEVEL
Static water level 65 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Leach Drilling Inc (Contractor)
Address Po Box 579 (Contractor)
Silver Springs NV 89429
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1677
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 7-30-93

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627