BW-2

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 42054
Permit No.
Basin 4-61

NOTICE OF INTENT NO.

1. OWNER BARRICK GOLDSTRIKE
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION NW ¼ SW ¼ Sec 19 T 36 N/~~X~~ R 50 E EUREKA County

PERMIT NO. 54371T (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
CIRCULATED BENTONITE MUD				
WITH AN 80 SECOND FUNNEL				
VISCOSITY FROM 1322 FEET TO				
SURFACE. CEMENTED TO 50 FEET.				
*NOTE: WELL WAS CUT-OFF				
APPROX. 300 FT FROM ORIGINAL				
COMPLETION AS AREA WAS MINED				
THROUGH. ALL DEPTHS GIVEN				
ARE WITH REFERENCE TO THE				
ORIGINALLY COMPLETED WELL.				

Date started JUNE 18, 1993
Date completed JUNE 19, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1322 Feet Depth Cased 1322 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
30	Inches	0	Feet	30	Feet
21	Inches	30	Feet	1322	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
22	87	.375	0	30
16	63	.375	0	1322

Perforations:
Type perforation ROSCOE MOSS FULL-FLOW
Size perforation
From 410 feet to 450 feet
From 470 feet to 710 feet
From 730 feet to 810 feet
From 830 feet to 870 feet
From 890 feet to 1310 feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☒ Poured

Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 1322 feet

9. WATER LEVEL
Static water level 1100 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1410

Signed [signature] (By driller performing actual drilling on site or contractor)

Date JUNE 19, 1993

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627