

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 23865

1. OWNER John and Juli Parker ADDRESS AT WELL LOCATION \_\_\_\_\_  
 MAILING ADDRESS 565 Sparks Blvd \_\_\_\_\_  
Sparks, Nv 89434 \_\_\_\_\_  
 2. LOCATION WEST NE 30 T. 21 N/S R. 21 E Washoe County  
 PERMIT NO. 076-380-37 \_\_\_\_\_  
 Issued by Water Resources \_\_\_\_\_ Parcel No. \_\_\_\_\_ Subdivision Name Spanish Springs

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Volcanic cobbles & boulders red green in color with D.G. sand		0	19	19
Red clay volcanic gravels with scattered boulders green & reddish brown		19	42	23
Reddish brown & green volcanic rock with white specs semi hard		42	68	26
Red brown green gravels with brown clay		68	118	50
Red clay brown green volcanic gravels		118	170	52
Light brown clay some volcanic gravels		170	266	96
Red volcanic rock semi hard		266	293	27
Green & reddish brown volcanic rock hard fractured		293	497	204

8. WELL CONSTRUCTION  
 Depth Drilled 497 Feet Depth Cased 497 Feet  
 HOLE DIAMETER (BIT SIZE)  

	From	To
10 5/8 Inches	0	57
8 1/2 Inches	57	340
6 1/4 Inches	340	497

 CASING SCHEDULE  

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+ 2	340
5	9.66	.188	330	497

 Perforations:  
 Type perforation factory  
 Size perforation 3732 X 3  
 From 457 feet to 477 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 58  Neat Cement  
 Placement Method:  Pumped  Concrete Grout  
 Poured  
 Gravel Packed:  Yes  No  
 From 58 feet to 340 feet

Date started T.D. 497 ft 9/23/93, 19\_\_\_\_\_  
 Date completed 9/28/93, 19\_\_\_\_\_  
 7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
15		3

9. WATER LEVEL  
 Static water level 340 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature cool °F Quality \_\_\_\_\_  
 10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Aqua Drilling & Well Service, Inc  
 Address 625 Spice Islands Dr Suite L  
Sparks, Nv 89431  
 Nevada contractor's license number 15291  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the 1511  
 Division of Water Resources, the on-site driller  
 Signed Roger [Signature]  
 By driller performing actual drilling on site or contractor  
 Date 9/30/93