WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 42949
Permit No.
Basin G-87

NOTICE OF INTENT NO. 21155

1. OWNER First Interstate Bank
MAILING ADDRESS 301 South Virginia Street Reno NV
ADDRESS AT WELL LOCATION Same

2. LOCATION NE ¼ SE ¼ Sec. 12 T. 19 N/S R. 19 E. Washoe County
PERMIT NO. MO 588 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other Tubex

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
the well was found to be in good condition. I removed the christy box, then, using five bags of type II portland cement, mixed at a ratio of one sack per six gallons of water, I pumped the cement slurry to the bottom of the casing using a one inch tremie pipe. I filled the pipe to the top then waited about 45 minutes for the slurry to set, topped off the hole and did site cleanup and left.				

Date started 8-13, 1993
Date completed 8-13, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

N/A

8. WELL CONSTRUCTION
Depth Drilled 60 Feet Depth Cased 60 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
5 Inches	0 Feet	50 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	Sch. 40	PVC	0	60

Perforations:
Type perforation Factory Slot
Size perforation .020
From feet to feet
From 37 feet to 60 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 34
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 34 feet to 60 feet

9. WATER LEVEL
Static water level 40.6 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature Cold °F Quality N/A

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Andersen Exploration Drilling (Contractor)
Address 1635 Belford Rd. Reno NV (Contractor) 89509
Nevada contractor's license number issued by the State Contractor's Board 34525
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1667
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 8-13-93

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627