WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 43728
Permit No.
Basin 6-85

NOTICE OF INTENT NO. 23375

1. OWNER EUGENE WHELCHEL
MAILING ADDRESS 5720 Bozic Lane
Sun Valley, NV 89433

ADDRESS AT WELL LOCATION 325 Alamosa
Sparks, NV 89436

2. LOCATION SW ¼ SW ¼ Sec. 12 T. 21N N/S R. 20 E. Washoe County
PERMIT NO. _____ Issued by Water Resources
076-290-36 Parcel No.
Spanish Springs Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Brown sandy clay		1	6	5
Brown sand		6	15	9
Browqn sandy clay		15	63	48
Brown clay		63	119	56
Weathered granite,soft		119	153	34
White granite		153	190	37
Gray granite		190	206	16
White granite		206	241	35
Soft zone	X	241	244	3
White granite		244	268	24
Fracture	X	268	269	1
White granite		269	290	21
Fracture granite		290	292	2
White granite		292	300	8

'93 DEC 29 AM 11:21
STATE ENGINEER

Date started 12-20-93, 19
Date completed 12-22-93, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 Inches	0 Feet	50 Feet
8 5/8 Inches	50 Feet	300 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	300

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 235 feet to 295 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 300 feet

9. WATER LEVEL
Static water level 190 feet below land surface
Artesian flow 75 G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. Contractor
Address P.O. Box 12370 Contractor
Reno, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed [signature] By driller performing actual drilling on site or contractor
Date December 26, 1993

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O) 627