WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 43795
Permit No.
Basin 7-92

NOTICE OF INTENT NO. 23396

1. OWNER JOHN & LORI BOHACH
MAILING ADDRESS 10505 Deodar Way
Reno, NV 89506

ADDRESS AT WELL LOCATION: Same

2. LOCATION SW ¼ NE ¼ Sec. 26 T 21N N/S R 19 E. Washoe County
PERMIT NO. (Issued by Water Resources) 080-285-10 (Parcel No.) Lemmon Valley (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☒ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
WELL DEEPENING:				
Total depth of well 112 feet.				
Static water level in well at 84.7 feet.				
Yield approximate 2 GPM				
Brown decomposed granite		112	135	23
Gray hard rock		135	147	12
Soft zone		147	151	4
Gray hard rock		151	164	13
Fractured rock, broken		164	171	7
Gray hard rock		171	176	5
Fractures at X176, 178, 186, 198, & 202 feet				
Soft zone	X	209	211	2
Gray hard rock		211	215	4
Fractures X at 215 &217				
Gray hard rock		221	224	3
Fractures Weathered	X	224		
Gray hard rock		229	232	3
FRacture	X	232		
Gray hard rock		240	256	16
Fractured rock	X	256		
Fractured	X	265		
Soft zone		271	282	11

NOTE: From 265 to 282 formation too soft, did not stay open. Caved in,

Date started 12-22-93, 19
Date completed 12-23-93, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 282 Feet Depth Cased 265 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
5½" Inches		112 Feet	282 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5" OD		.188	0	198
3" OD		sch 40	197	265

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 118 feet to 138 feet
From 158 feet to 198 feet
From 223 3" OD feet to 225 torch cut feet
From 233 feet to 235 feet
From 245 feet to 265 feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal N/A
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☒ No too tight
From feet to feet

9. WATER LEVEL
Static water level 84.7 feet below land surface
Artesian flow 12 G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, NV 89510

Nevada contractor's license number 22549 issued by the State Contractor's Board
Nevada driller's license number 908 issued by the Division of Water Resources, the on-site driller.

Signed (By driller performing actual drilling on site or contractor)
Date December 27, 1993

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627