WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 43211
Permit No.
Basin 8-102

NOTICE OF INTENT NO. 23419

1. OWNER Jack Able
MAILING ADDRESS 800 E. Graves Lane
Carson City, Nevada 89706

ADDRESS AT WELL LOCATION 2905 Ramsey
Silver Springs, NV. 89429

2. LOCATION SW ¼ SW ¼ Sec. 35 T. 18 N/S R. 24 E. Lyon County
PERMIT NO. N/A (Issued by Water Resources) Parcel No. 15-211-32 Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☑ Air ☑ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Soil and Some Rock		0	10	10
Tan Clay		10	105	95
Brown Clay		105	145	40
Gray Clay		145	160	15
Gray Clay And Rock mixed		260	280	20
Black Shale with Gravels		280	350	70
Gray Clay		350	355	5
Black Shale	✓	355	400	45

Date started 11-10, 1993
Date completed 11-11, 1993

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Developed For about		hours
And produced about		Gallons A min.

8. WELL CONSTRUCTION
Depth Drilled 400 Feet Depth Cased 400 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
18 5/8	0	60
8 3/4	60	400

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.00	3/16	+1	400

Perforations:
Type perforation Factory Cut
Size perforation 3x1¼ x 3 6 Rows
From 300 feet to 320 feet
From 380 feet to 400 feet
From ... feet to ... feet
From ... feet to ... feet
From ... feet to ... feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-60
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 60 feet to 400 feet

9. WATER LEVEL
Static water level 174 feet below land surface
Artesian flow ... G.P.M. ... P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Leach Drilling Inc (Contractor)
Address Po Box 599 Silver Springs NV 89429 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board # 0031841
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1877
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 11-22-93

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627