WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 43526
Permit No.
Basin 11-195

NOTICE OF INTENT NO. 24119

1. OWNER Baker Sewer & Water Dept.
MAILING ADDRESS P.O. Box 165
Baker, NV 89311

ADDRESS AT WELL LOCATION
Proposed Treatment Plant Hole #3
Baker, NV

2. LOCATION NE ¼ SE ¼ Sec. 4 T. 13 (N) S R. 70 E. White Pine County

PERMIT NO. Waiver #M/O-747 (Issued by Water Resources) | NA (Parcel No.) | NA (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay		0	13	13
Coarse sand & gravel		13	17	4
Clay/gravel		17	26	9

'94 JAN 13 A11:23
STATE ENGINEER'S OFFICE

Date started December 20, 19 93
Date completed December 20, 19 93

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
	did not test	

8. WELL CONSTRUCTION
Depth Drilled 26 Feet Depth Cased 26 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
7 7/8 Inches		0 Feet	26 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		PVC SCH 40	+2	11
2		PVC SCH 40	21	26

Perforations:
Type perforation Triple row mill slot
Size perforation 1/8 X 2½
From 11 feet to 21 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 8
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout
*Bentonite Seal from 8'-9'
Gravel Packed: [X] Yes [ ] No
From 9 feet to 26 feet

9. WATER LEVEL
Static water level 13 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 590 (Contractor)
Winnemucca, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1562
Signed C. E. Epple (By driller performing actual drilling on site or contractor)
Date 1-12-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627