WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

27810

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 43763
Permit No.
Basin 7-95

NOTICE OF INTENT NO. 23785

1. OWNER Greg Jaeger
MAILING ADDRESS 100 Filer Rd
Reno, Nv 89506

ADDRESS AT WELL LOCATION 1390 ~~Roth Rd~~ Hall's Mine Rd
Parcel 3

2. LOCATION NE ¼ nw ¼ Sec. 27 T. 22 N/S R. 19 E. Washoe County
PERMIT NO. — (Issued by Water Resources) 079-450-29 (Parcel No.) — Antelope Valley Rockfield (#1891 part 3) (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Tan clay with tan | | | | |
| yellow white brown | | | | |
| green D.G. sands | | 0 | 11 | 11 |
| Green white granite | | | | |
| hard | | 11 | 18 | 7 |
| Semi decomposed | | | | |
| granite fractured | | | | |
| hard | | 18 | 68 | 50 |
| Hard fractured granite | | | | |
| dark green white & | | | | |
| light green | | 68 | 438 | 370 |
| T.D. 438 ft | | | | |

'93 OCT 28 P1:03 RECEIVED STATE ENGINEER'S OFFICE

Date started 10/15/93, 19
Date completed 10/21/93, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 20+ | | 2 |

8. WELL CONSTRUCTION
Depth Drilled 438 Feet Depth Cased 438 Feet

HOLE DIAMETER (BIT SIZE)

| Inches | From (Feet) | To (Feet) |
|---|---|---|
| 10 5/8 | 0 | 51 |
| 8 ½ | 51 | 438 |
| | | |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6 5/8 | 12.92 | .188 | + 1 | 438 |

Perforations:
Type perforation factory
Size perforation 3/32 X 3
From 418 feet to 438 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 438 feet

9. WATER LEVEL
Static water level 260 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Aqua Drilling & Well Service, Inc (Contractor)
Address 625 Spice Islands Dr Suite L (Contractor)
Sparks, Nv 89431
Nevada contractor's license number issued by the State Contractor's Board 15291
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1511
Signed Roger M. Thrall (By driller performing actual drilling on site or contractor)
Date Roger M. Thrall 10/22/93

(Rev. 3 91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627