WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 43809
Permit No.
Basin 9-108

NOTICE OF INTENT NO. 20236

1. OWNER Robert Butterfield
MAILING ADDRESS 211 South C Street
Lompoc, Ca. 93436

ADDRESS AT WELL LOCATION 245 Hwy 95A East
Yerington, Nv

2. LOCATION NE ¼ SE ¼ Sec. 18 T. 13 N/S R. 26 E. Lyon County

PERMIT NO. (Issued by Water Resources) | 14-561-16 (Parcel No.) | None (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☒ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SAND		0'	2'	2'
Clay & Silt		2'	12'	10'
Clay		12'	16'	4'
Gravel & Clay		16'	20'	4'
Clay		20'	28'	8'
Gravel & Clay		28'	34'	6'
Clay		34'	55'	21'
Sand		55'	60'	5'
Clay		60'	80'	20'
Gravel & Sand	X	80'	110'	30'
Clay		110'		

'93 NOV -3 A10:31 STATE ENGINEERS OFFICE

Date started 21 Oct, 1993
Date completed 30 Oct, 1993

7. WELL TEST DATA

TEST METHOD: ☒ Bailer ☒ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Bailer	10	-0-	3
Pump	30	-0-	4

8. WELL CONSTRUCTION
Depth Drilled 110 Feet Depth Cased 110 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 Inches		0 Feet	52 Feet
6 Inches		0 Feet	110 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.77	.188	0	110'

Perforations:
Type perforation machined
Size perforation 1/8 X 3
From 108' feet to 102 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☒ Pumped ☐ Poured

Seal Type: ☐ Neat Cement ☒ Cement Grout ☒ Concrete Grout

Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 53 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Vernon Cannon Jr. (Contractor)
Address 4555 Hwy 50 W (Contractor)
Silver Springs, Nv 89429

Nevada contractor's license number issued by the State Contractor's Board 23317

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1455

Signed Vernon Cannon Jr. (By driller performing actual drilling on site or contractor)
Date 30 Oct 93

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627