PPW-34

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44073
Permit No.
Basin 4-61

NOTICE OF INTENT NO. 26418

1. OWNER BARRICK GOLDSTRIKE MINE
MAILING ADDRESS P.O. BOX 29
ELKO NEVADA 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION NE ¼ SW ¼ Sec 19 T 36 N/S R 50 E EUREKA County
PERMIT NO. 55140 Issued by Water Resources | N/A Parcel No. | N/A Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BLACK CLAY		0	4	4
BLACK CLAY & ROCK		4	55	51
BLACK ROCK FRACTURED		55	320	265
BLACK & GRAY ROCK	X	320	338	18
BLACK ROCK	X	338	380	42
GRAY CLAY & ROCK		380	420	40
BLACK ROCK	X	420	460	40
BLACK & GRAY ROCK		460	500	40
GRAY CLAY & BROWN ROCKXX		500	560	60
BLACK ROCK	X	560	690	130
BROWN ROCK & RED CLAY	X	690	805	115
BLACK ROCK & CLAY		805	1020	215

Date started MARCH 10, 19 94
Date completed MARCH 17, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1,020 Feet Depth Cased 1,000 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12-1/4	Inches	0 Feet	60 Feet
7-7/8	Inches	60 Feet	340 Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	24.7	.322	0	60
4	18	SCH 80	0	340

Perforations:
Type perforation SLOT
Size perforation 1/8
From 340 feet to 1000 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 240
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 240 feet to 1,020 feet

9. WATER LEVEL
Static water level FLOWING feet below land surface
Artesian flow 100 G.P.M. 18 P.S.I.
Water temperature 100 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LANG EXPLORATORY DRILLING Contractor
Address 2286 WEST 1500 SOUTH Contractor
SALT LAKE CITY UT 84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1829
Signed [signature] By driller performing actual drilling on site or contractor
Date 3-24-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627