WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44306
Permit No.
Basin Ø 87

NOTICE OF INTENT NO. 17561

1. ~~OWNER~~ Consultant: ERM-West, Inc.
MAILING ADDRESS 2001 P Street, Suite 200
Sacramento, CA 95814-5213

ADDRESS AT WELL LOCATION Catelius Corp
1235 Glendale Ave
Sparks, NV

2. LOCATION SW ¼ NE ¼ Sec. 8 T 19N N/S R 20 E Washoe County
PERMIT NO. M/O#Pending 392 (Issued by Water Resources) | MW#3 (Parcel No.) | Sparks,NV (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	½	½
Clay, gravel mix		½	2	1½
Boulders, rounded, up to 12" dia. some clay		2	4	2
Clay, dark gray, moist		4	10½	6½
Gravel, cobbles to 6" dia., to coarse sands		10½	24.4	13.9

Date started 5-2-91, 19
Date completed 5-2-91, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 24.4 Feet Depth Cased 24.4 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 5/16 Inches		0 Feet	24.4 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		sch 40	0	24.4
4" PVC	srew cap			
4" PVC	security cap			

Perforations:
Type perforation factory sawed slot
Size perforation 0.020 x 1½ x 6 rows
From 9 feet to 24 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 5 ft
Placement Method: [ ] Pumped [X] Poured
Bentonite: 2
Gravel Packed: [X] Yes [ ] No
From 7 feet to 24.4 feet

Seal Type:
[X] Neat Cement
[ ] Cement Grout
[ ] Concrete Grout

9. WATER LEVEL
Static water level 12.72 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date April 7, 1994

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627