WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 44437
Permit No.
Basin 059

NOTICE OF INTENT NO. 19229

1. OWNER Echo Bay Minerals
MAILING ADDRESS P.O. Box 1658
Battle Mtn Nevada 89820
ADDRESS AT WELL LOCATION McCoy mine

2. LOCATION NE ¼ SE ¼ Sec. 35 T. 29 N/S R. 42 E. Lander County
PERMIT NO. m/o 372 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Limestone | | 0 | 980 | |
| conglomerate | X | 980 | 1200 | |
| fractured | | | | |
| Limestone At | | | | |
| 960 - 990 | | | | |
| contains some | | | | |
| water, conglomerate | | | | |
| At 1000 - 1090 | | | | |
| contains 70-80 gpm | | | | |

Date started April 13, 1994
Date completed April 15, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 70-80 gpm At | Depth | |

8. WELL CONSTRUCTION
Depth Drilled 1300 Feet Depth Cased 1300 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 6 Inches | 0 Feet | 1300 Feet | |
| Inches | Feet | Feet | |
| Inches | Feet | Feet | |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 2 | pvc | sch 80 | 0 | 1300 |
| | | | | |

Perforations:
Type perforation slotted
Size perforation .010
From 0 feet to 1220 Blank feet
From screen 1220 feet to 1280 feet
From Blank 1280 feet to 1300 feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 180
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 1300 feet to 1160 feet

9. WATER LEVEL
Static water level 913 feet below land surface
Artesian flow G.P.M. — P.S.I.
Water temperature 100 °F Quality Fair

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name EKLund Drilling Inc. (Contractor)
Address P.O Box 2786 (Contractor)
Elko NV 89803
Nevada contractor's license number issued by the State Contractor's Board # 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller # 1759
Signed Tom Kouis (By driller performing actual drilling on site or contractor)
Date April 20, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627