WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45077
Permit No.
Basin 131

NOTICE OF INTENT NO. 26888

1. OWNER Battle Mountain Gold
MAILING ADDRESS P.O. Box 1627
Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION Hole #CM-27
Battle Mountain Gold

2. LOCATION NW ¼ NW ¼ Sec. 3 T 30 N/S R 43 E Lander County
PERMIT NO. M/O-651 Issued by Water Resources | NA Parcel No. | NA Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvian		0	8	8
Coarse sand		8	28	20
Alluvian		28	278	250
Volcanic basalt		278	388	110
***Bentonite & silica sand from 50'-60'				

Date started May 23, 1994
Date completed May 25, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1		4

8. WELL CONSTRUCTION
Depth Drilled 388 Feet Depth Cased 385 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6 1/4 Inches	0 Feet	388 Feet	
Inches	Feet	Feet	
Inches	Feet	Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	PVC	SCH 80	0	305
2	PVC	SCH 80	365	385
1	PVC	SCH 80	0	305
1	PVC	SCH 80	365	385

Perforations:
Type perforation .050 PVC Screen
Size perforation SCH 80
From 2" 305 feet to 365 feet
From 1" 305 feet to 365 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 60 feet to 385 feet

9. WATER LEVEL
Static water level 300 feet ~~below land surface~~ from top of casing.
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. Contractor
Address P.O. Box 590 Contractor
Winnemucca, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed C. E. Epple
By driller performing actual drilling on site or contractor
Date 6-21-94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627