PPW41

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45097
Permit No. 55146
Basin 4-061

NOTICE OF INTENT NO. 26407

1. OWNER BARRICK GOLDSTRIKE MINE
MAILING ADDRESS P.O. BOX 29
ELKO NEVADA 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION NW ¼ NW ¼ Sec. 30 T 36 N/S R 50 E EUREKA County
PERMIT NO. 55146 (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☒ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
GREEN-GRAY CLAY		0	48	
GREEN-GRAY ROCK		48	80	
GRREN-GRAY ROCK CLAY		80	95	
GREEN GRAY ROCK HARD		95	195	
GREEN-GRAY BROKEN		195	210	
GREEN-GRAY ROCK		210	230	
GREEN-GRAY BROKEN		230	290	
GREEN-GRAY HARD		290	370	
GREEN-GRAY BROKEN		370	405	
GRAY & BLACK		405	440	
GRAY-GREEN BLACK				
BROKEN		440	485	
GRAY-GREEN BLACK				
ROCK & CLAY		485	500	
GRAY&BLACK ROCK		500	520	

'94 JUN 23 A11:57 STATE ENGINEER

Date started MARCH 26, 19 94
Date completed MARCH 28, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 520 Feet Depth Cased 515 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
19 Inches		0 Feet	20 Feet
8 Inches		20 Feet	520 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
14	55	3/8	0	20
4	18	SCH80	0	315

Perforations:
Type perforation SLOT
Size perforation 1/8"
From 315 feet to 515 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 310 feet to 520 feet

9. WATER LEVEL
Static water level 481 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature 60 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UT, 84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1728
Signed Jim Lane (By driller performing actual drilling on site or contractor)
Date 04/18/94

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627