WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

**Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340**

OFFICE USE ONLY
Log No. 45267
Permit No.
Basin 129

NOTICE OF INTENT NO. 26905

1. OWNER Coeur Rochester
MAILING ADDRESS P.O. Box 1057
Lovelock, NV 89419

ADDRESS AT WELL LOCATION Hole #3
Coeur Rochester Mine
25 miles SE of Lovelock

2. LOCATION NW ¼ SW ¼ Sec. 11 T. 28 (N)S R. 34 E. Pershing County
PERMIT NO. M/O-801 (Issued by Water Resources) | NA (Parcel No.) | NA (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Alluvial fill | | 0 | 29 | 29 |
| Fractured bedrock | | 29 | 39 | 10 |

Date started June 2, 1994
Date completed June 3, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

8. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 39 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 7 7/8 Inches | 0 Feet | 40 Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 4 | SCH 40 | PVC | 0 | 29 |
| | | | | |
| | | | | |

Perforations:
Type perforation 4" PVC Screen
Size perforation .020 slot
From 29 feet to 39 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 22'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 22 feet to 39 feet

9. WATER LEVEL
Static water level 17.2 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature norm °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 590 (Contractor)
Winnemucca, NV 89446
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1562
Signed (By driller performing actual drilling on site or contractor)
Date 7-7-94

STATE ENGINEER
94 AUG 29 P3:37

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627