WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45452
Permit No.
Basin 212

NOTICE OF INTENT NO. 13082

1. OWNER Broadbent & Assoc c/o Westwood Financial
MAILING ADDRESS 11440 San Vicente Ste 200 Los Angeles CA 90049
ADDRESS AT WELL LOCATION Sun Express 1562 North Eastern, Las Vegas, NV

2. LOCATION NW ¼ NW ¼ Sec. 25 T. 21 N/S R. 61 E. Clark County
PERMIT NO. M0-2434 (Issued by Water Resources) 060-470-007 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE S-1
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay		0	29	29

RECEIVED
JUN 9 1994
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started April 14, 19 94
Date completed April 14, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 29 Feet Depth Cased 29 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
8	0	29

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.64	0.157	0	29

Perforations:
Type perforation Factory slot
Size perforation 0.020
From 24 feet to 29 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 3'-21', 21'-23' Bentonite
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 23 feet to 29 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Thomas High (Contractor)
Address 4670 So. Polaris Ave. Las Vegas, NV 89103 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1869
Signed Tom High (By driller performing actual drilling on site or contractor)
Date May 27, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45452
Permit No.
Basin 212

NOTICE OF INTENT NO. 13082

1. OWNER BROADBENT + ASSOC % WESTWOOD FINANCIAL
MAILING ADDRESS 11440 SAN VICENTE STE. 200 LOS ANGELES, CA 90049
ADDRESS AT WELL LOCATION SUN EXPRESS 1562 NORTH EASTERN AVE, LAS VEGAS NV

2. LOCATION NW ¼ NW ¼ Sec. 25 T. 21 N/S R. 61 E. CLARK County
PERMIT NO. MO-2434 (Issued by Water Resources) 060-470-007 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE V-2
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other AUGER

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SAND - SILT - CLAY (ML)		0	10	10
SILTY CLAY		10	19	9

RECEIVED
JUN 9 1994
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started APRIL 15, 1994
Date completed APRIL 15, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 19 Feet Depth Cased 19 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	19 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	1.9	0.237	0	19

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020
From 9 feet to 19 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 3'-6'; 6'-8' Bentonite
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 8 feet to 19 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name THOMAS HEGA (Contractor)
Address 4670 SO. POLARIS AVE. (Contractor)
LAS VEGAS, NV 89103
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1869
Signed Tom (By driller performing actual drilling on site or contractor)
Date MAY 27, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627