WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45486
Permit No.
Basin: 212

NOTICE OF INTENT NO. 13060

1. OWNER CAL NEV PIPELINE
MAILING ADDRESS 412 W. HOSPITALITY STE 202 P.O. BOX 6346, SAN BERNARDINO, CA 92412
ADDRESS AT WELL LOCATION INTERSECTION OF HACIENDA & VALLEY VIEW

2. LOCATION SE ¼ NE ¼ Sec. 30 T 21 N/S R 61 E CLARK County
PERMIT NO. M0-2400 Issued by Water Resources | CL ROW Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE MW-15
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SILTY SAND		0	14	14
CALICHE		14	17	3
SILTY SAND		17	18	1
CALICHE		18	20	2
SILTY SAND		20	22	2
SILTY CLAY		22	28	6
SILT		28	32	4
CLAYEY SILT		32	33	1
SILTY SAND		33	39	6
CALICHE		39	43	4
CLAYEY SAND		43	45	2
SILTY SAND		45	48	3
CALICHE		48	53	5
SILTY TO CLAYEY SAND		53	64	11
CALICHE		64	67	3
CLAY		67	75	8

RECEIVED
MAR 17 1994
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started FEBRUARY 24, 19 94
Date completed FEBRUARY 24, 19 94

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 75 Feet Depth Cased 75 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 Inches	0 Feet	75 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.64	0.154	0	75

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020
From 50 feet to 75 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0-42'/42-47' BENTONITE
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 47 feet to 75 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name DONALD WILSON
Address 4670 SO. POLARIS AVE (Contractor)
LAS VEGAS NV 89103 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1589
Signed Donald T. Wilson (By driller performing actual drilling on site or contractor)
Date MARCH 15, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627