WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45650
Permit No.
Basin 212

NOTICE OF INTENT NO. 13112

1. OWNER UNITED PARCEL SERVICE
MAILING ADDRESS 740 MARTIN LUTHER KING BLVD LAS VEGAS, NV 89106
ADDRESS AT WELL LOCATION UNITED PARCEL SERV 740 MARTIN LUTHER KING BLVD. LAS VEGAS, NV 89106

2. LOCATION NW ¼ SE ¼ Sec. 28 T. 20 N/S R. 61 E. CLARK County
PERMIT NO. MO-2433 (Issued by Water Resources) 139-28-703-001 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE MW-2
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
FILL: clayey silty sand and pea gravel		0'	3'	3'
SANDY SILT		3'	6'	3'
CALICHE		6'	7'	1'
SILTY, CLAYEY SAND		7'	11.5'	4.5'
CALICHE		11.5'	14'	2.5'
SANDY, SILTY CLAY		14'	16'	2'
SANDY LEAN CLAY		16'	20'	4'
LEAN CLAY		20'	22.5'	2.5'

RECEIVED
AUG 02 1994
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started JUNE 2, 1994
Date completed JUNE 2, 1994

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 22.5 Feet Depth Cased 22.5 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
6"	0	22.5

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.64	0.154	0	22.5

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020"
From 19 feet to 22 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-15.5', 15.5-18.5' bentonite pellets
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 18.5 feet to 22.5 feet

9. WATER LEVEL 6-28-94
Static water level 12.1 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name DON WILSON
Contractor
Address 4670 S. POLARIS AVE.
Contractor
LAS VEGAS, NV 89103
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1589
Signed Donald J. [illegible]
By driller performing actual drilling on site or contractor
Date July 28 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627