WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 45835
Permit No.
Basin 087

NOTICE OF INTENT NO. 12887

1. ~~OWNER~~ Consultant: Certified Enviromental Consulting Inc.
MAILING ADDRESS 4562 East 2nd Street, Suite A
Benicia, CA. 94510

ADDRESS AT WELL LOCATION Bill Pierce Olds.
2100 Kietzke Ln.
Reno, NV.

2. LOCATION NW ¼ NW ¼ Sec. 19 T 19N N/S R 20 E Washoe County
PERMIT NO. M/O# ~~zone~~ 2444 assigned (Issued by Water Resources) - Well PRW-22 (Parcel No.) Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [X] Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill		0	1	1
Brown Clay		1	7	6
Sandy clay w/sm gravel	X	7	14	7
Sand & sm gravel	X	14	16	2
Sand & lgr gravel	X	16	18	2
Sand & sm gravel	X	18	25	7
Gray clay		25	27	2
Sandy brn clay mixed w/ sm gravel		27	28	1
Broken brn rock w/ some clay & gravel		28	29	1

'94 SEP 19 P4:20
STATE ENGINEERS OFF

Date started July 28, 1989, 19
Date completed July 28, 1989, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 29 Feet Depth Cased 29 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
9 5/16	0	29

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5" PVC		sch 40	0	29

Perforations:
Type perforation factory sawed slot
Size perforation .020
From 9 feet to 29 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0 - 5 feet
Placement Method: [X] Pumped [ ] Poured
Bentonite seal 5 - 7 feet
Gravel Packed: [X] Yes [ ] No
From 7 feet to 29 feet

Seal Type:
[X] Neat Cement
[ ] Cement Grout
[ ] Concrete Grout

9. WATER LEVEL
Static water level not known feet below land surface
Artesian flow G.P.M. n/a P.S.I.
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date March 9, 1993

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627