WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

**Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340**

OFFICE USE ONLY
Log No. 45841
Permit No.
Basin 0928

NOTICE OF INTENT NO. 22850

1. OWNER JOHN KERNS
MAILING ADDRESS 9350 Tomahawk
Reno, NV 89506

ADDRESS AT WELL LOCATION Same

2. LOCATION SW ¼ NE ¼ Sec. 11 T. 20N N/S R. 19 E Washoe County
PERMIT NO. (Issued by Water Resources) 082-211-06 (Parcel No.) Golden Valley (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☒ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| WELL DEEPENING: | | | | |
| Weathered granite | | 177 | 212 | 35 |
| Soft zone (app. 3 GPM) | X | 212 | 218 | 7 |
| Weathered grnite | | 218 | 235 | 17 |
| Gray granite | | 235 | 256 | 21 |
| Fracture (app. 2 GPM) | X | 256 | 257 | 1 |
| Gray granite | | 257 | 317 | 60 |
| Soft zone, weathered granite NO WATER | | 317 | 322 | 5 |
| Gray granite | | 322 | 355 | 33 |
| Fracture (app. 2 GPM) | X | 355 | 356 | 1 |
| Gray granite | | 356 | 369 | 13 |
| Fracture (app. 1 GPM) | X | 369 | 370 | 1 |
| Gray grnaite | | 370 | 377 | 7 |

Date started 6-30-94, 19
Date completed 6-30-94, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 9+ | | |

8. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 377 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 6 1/8 Inches | 177 Feet | 377 Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 5" OD | | .188 | 166 | 377 |

Perforations:
Type perforation factory sawd slot
Size perforation 3/32 x 3 x 5 around
From 206 feet to 226 feet
From 266 feet to 286 feet
From 346 feet to 366 feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal deepening
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 155 feet below land surface
Artesian flow G.P.M. 9+ P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed (By driller performing actual drilling on site or contractor)
Date July 8, 1994

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-077